

**ROTANODE™
XRR-6653X****Rotating Anode X-ray Tube Assembly**

- ◆ High speed rotating anode X-ray tube assembly for high energy radiographic operations.
- ◆ For the purpose of general diagnostic X-ray procedures.
- ◆ This tube has foci 0.8 and 0.3, and is available for a maximum tube voltage 150 kV.
- ◆ The anode disk is constructed with specially processed rhenium-tungsten-faced molybdenum target of 100 mm diameter.

**General Data**

IEC Classification (IEC60601-1:2005+A1:2012) Class I ME EQUIPMENT

Electrical:

Circuit:

High Voltage Generator	Constant Potential High-Voltage Generator
Grounding	Center-Grounded

Nominal X-ray Tube Voltage:

Radiographic	150 kV
--------------------	--------

Nominal Focal Spot Value:

Large Focus	0.8
Small Focus	0.3

Nominal Anode Input Power (at 0.1s) See rating charts

	180 Hz	60 Hz	50 Hz
Large Focus	52 kW	30 kW	29 kW
Small Focus	12 kW	6.5 kW	6.1 kW

Nominal Radiographic Anode Input Power:

	180 Hz	60 Hz	50 Hz
Large Focus	52 kW	30 kW	29 kW
Small Focus	12 kW	6.5 kW	6.1 kW

★The information contained herein is presented only as a guide for the application of our products. No responsibility is assumed by Canon Electron Tubes & Devices Co., Ltd. (CETD) for any infringements of patents or other rights of the third parties which may result from its use.

No license is granted by implication or otherwise under any patent or patent rights of CETD or others.

★The information contained herein may be changed without prior notice. It is therefore, advisable to contact to CETD before processing with the design of equipment incorporating this product.

Motor Ratings:

Stator: XS-AG

		Starting		Running	
Driven Frequency	[Hz]	180	60	180	50/60
Input Power	[W]	3710	800	200	90
Voltage ^{3) 5)}	[V]	420	190	80	48
Current ⁴⁾	[A]	9.6	10.2	3.0	2.2
Min. Speed Up ^{1) 7)}	[s]	1.2	0.8	-	-
Capacitor	[μF]	6	44	6	44
Min. Braking ^{2) 7)}	[s]	2.0 (DC 100V)			

- Note 1) The speed up time from normal speed to high speed is 2/3 times of the specified speed up time from 0 to high speed, which is described on motor rating table.
 2) To be applied for high speed rotation.
 3) Applied voltage between common and main terminal.
 4) Common current.
 5) The every applied voltage must be never exceeded 110% of the above specification.
 6) No more than two high speed starts per minute are permissible.
 7) The speed-up time is allowed up to 110% of the above specification.

Anode Speed:

180 Hz	Minimum 9700 min ⁻¹
60 Hz	Minimum 3200 min ⁻¹
50 Hz	Minimum 2700 min ⁻¹

Stator Resistance:

Common-Main Winding	9.4 Ω
Common-Auxiliary Winding	28.3 Ω

Resistance between Housing and Low Voltage Terminals

Minimum 2 MΩ

Normal Operating Range of the Housing Temperature

16 ~ 75 °C

Mode of Operation

Intermittent

Mechanical:

Dimensions	See dimensional outline
Overall Length	445 mm
Maximum Diameter	166 mm

Target:

Anode Angle	12 degrees
Diameter	100 mm
Construction	Rhenium-Tungsten faced Molybdenum

Permanent Filtration

1.5 mm Al / 75 kV IEC60522:1999

Radiation Protection (In accordance with IEC60601-1-3:2008):

Leakage Technique Factor

150 kV, 2 mA

X-ray Coverage

430 × 430 mm at SID 1000 mm

Weight

Approx. 20 kg

High Voltage Receptacle

To meet the requirements of IEC60526 Corrigendum1:2010

Cooling Method

Natural or Forced Air

Housing Model Number

XH-1031

Absolute Maximum and Minimum Ratings

(At any time, these values must not be exceeded.)

Maximum X-ray Tube Voltage:

Radiographic	150 kV
Between Anode (or Cathode) and Ground	75 kV
Minimum X-ray Tube Voltage	40 kV

Maximum X-ray Tube Current:

Large Focus	700 mA
Small Focus	150 mA

Maximum Filament Current:

Large Focus	5.5 A
Small Focus	5.0 A

Filament Voltage:

Large Focus (At maximum filament current 5.5 A)	11.6 ~ 14.8 V
Small Focus (At maximum filament current 5.0 A)	4.6 ~ 5.8 V
Filament Frequency Limits	0 ~ 25 kHz
Continuous Anode Input Power	500 W (700 HU/s)
(Fluoroscopic, Radiographic or mixed exposure)	

Thermal Characteristics:

Anode Heat Content	420 kJ (600 kHU)
Maximum Anode Heat Dissipation	1670 W (2300 HU/s)
X-ray Tube Assembly Heat Content	1480 kJ (2000 kHU)

Nominal Continuous Input Power:

Without Air-circulator	222 W (18 kHU/min)
------------------------------	--------------------

Environmental Limits

Operating Limits:

Temperature	10 ~ 40 °C
Humidity	30 ~ 85 %
	(No condensation)

Atmospheric Pressure	70 ~ 106 kPa
----------------------------	--------------

Shipping and Storage Limits:


Temperature	-20 ~ 70 °C
Humidity	20 ~ 90 %
	(No condensation)

Atmospheric Pressure	50 ~ 106 kPa
----------------------------	--------------


Maximum Rating Charts (Absolute Maximum Rating Charts)

Conditions: Tube Voltage
Constant potential high-voltage generator
Stator Power Frequency 180Hz

Nominal Focal Spot Value: 0.8 ■




Nominal Focal Spot Value: 0.3 □




Maximum Rating Charts (Absolute Maximum Rating Charts)

Conditions: Tube Voltage
Constant potential high-voltage generator
Stator Power Frequency 60Hz

Nominal Focal Spot Value: 0.8 ■




Nominal Focal Spot Value: 0.3 □




Maximum Rating Charts (Absolute Maximum Rating Charts)

Conditions: Tube Voltage
Constant potential high-voltage generator
Stator Power Frequency 50Hz

Nominal Focal Spot Value: 0.8 ■




Nominal Focal Spot Value: 0.3 □



Emission & Filament Characteristics


Constant potential high-voltage generator

Nominal Focal Spot Value: 0.8 ■



For Reference Only


Nominal Focal Spot Value: 0.3 □




For Reference Only

Thermal Characteristics

X-ray Tube Assembly Heating / Cooling Curve





Anode Heating / Cooling Curve




Dimensional Outline

Unit: mm




TERMINAL CONNECTIONS



TR TEMPERATURE RELAY
OPERATION TEMPERATURE
Open at $70(\pm 3)^\circ\text{C}$ or more
DIFFERENTIAL 10°C

CONNECTOR(AMP)
Cap 172157-1
Pin 170364-1



EXPLANATION OF SYMBOLS

CATHODE TERMINAL

- C : COMMON
- L : LARGE FOCUS
- S : SMALL FOCUS

TERMINAL CONNECTIONS

- C1 : COMMON
- M : MAIN WINDING OF THE STATOR
- A : AUX. WINDING OF THE STATOR
- NC : NON-CONNECTION
- ET : EARTH TERMINAL

TR : TEMPERATURE RELAY

▲ : CENTRAL X-RAY

ANODE & CATHODE TERMINAL

: IEC60526 TYPE

CANON ELECTRON TUBES & DEVICES CO., LTD.
Marketing Engineering Department, Sales Division
1385, Shimoishigami, Otawara-shi, Tochigi 324-8550, Japan
Tel +81-287-26-6666 Fax +81-287-26-6060
<https://etd.canon>